

Parama sintetica TK

Specificatii tehnice

Material: poliester si polipropilena
Standard: EN 919; EN 10556
Construcie: 8 fire impletite (4x2)
Utilizari: remorcare, offshore
Certificari: Lloyd`s Register si GL



| Diametru (mm) | Greutate (g/m) | Rezistenta (kg) | Rezistenta (kN) |
|---------------|----------------|-----------------|-----------------|
| 36 | 717 | 29100 | 285,5 |
| 40 | 885 | 35860 | 351,8 |
| 44 | 1070 | 42990 | 421,8 |
| 48 | 1270 | 49950 | 490 |
| 52 | 1500 | 57800 | 567 |
| 56 | 1730 | 66180 | 649,3 |
| 60 | 1990 | 75640 | 742 |
| 64 | 2270 | 85630 | 840 |
| 68 | 2560 | 95960 | 941,3 |
| 72 | 2870 | 107570 | 1055,3 |
| 76 | 3200 | 119880 | 1176 |
| 80 | 3540 | 132190 | 1296,8 |
| 88 | 4280 | 158590 | 1555,8 |
| 96 | 5100 | 183990 | 1805 |

| | |
|--|------------------------------|
| Densitate | 1.14 g/cm³ |
| Flotabilitate | NU |
| Temperatura maxima | 120°C |
| Rezistenta UV | Foarte buna |
| Rezistenta la acizi | Buna |
| Rezistenta la baze | Buna |
| Rezistenta la solventi organici | Foarte buna |